



VSM300 Primary Replacement Screen

Specifications & Dimensions

Fits shaker machines:	Brandt Thule
Quantity per shaker:	4
Type of Screen:	Pretension
Gasket:	No
Weight:	27 pounds (12.25 kg)
Approx. Dimensions:	27" X 35 3/8"

Mesh & API Information

CWC Mesh Type	CWC Mesh Size	API RP 13C Designation	D100 Cut Points (Microns)	API Micron Range for Screen Designation	Continental Wire Cloth Item #
Oblong	60	API 50	321	275-327.50	FR-VSP300CRX060
Oblong	84	API 60	233	231-275	FR-VSP300CRX084
Oblong	110	API 70	207	196-231	FR-VSP300CRX110
Oblong	140	API 80	172	165-196	FR-VSP300CRX140
Oblong	175	API 100	139	137.50-165	FR-VSP300CRX175
Oblong	210	API 120	131	116.50-137.50	FR-VSP300CRX210
Oblong	250	API 140	101	98-116.50	FR-VSP300CRX250
Oblong	270	API 170	86	82.5-98	FR-VSP300CRX270*
Oblong	325	API 200	73	69-82.5	FR-VSP300CRX325
Oblong	400	API 230	67	58-69	FR-VSP300CRX400
Square	24	API 20	861	780-925	FR-VSP300UF024
Square	38	API 35	521	462.5-550	FR-VSP300UF038
Square	50	API 45	373	327.5-390	FR-VSP300UF050
Square	70	API 60	263	231-275	FR-VSP300UF070
Square	84	API 70	212	196-231	FR-VSP300UF084
Square	110	API 80	185	165-196	FR-VSP300UF110
Square	140	API 100	150	137.5-165	FR-VSP300UF140
Square	175	API 120	125	116.5-137.5	FR-VSP300UF175
Square	210	API 140	106	98-116.5	FR-VSP300UF210
Square	230	API 170	90	82.5-98	FR-VSP300UF230
Square	250	API 200	76	82.5-98	FR-VSP300UF250*
Square	325	API 230	66	58-69	FR-VSP300UF325
Square	350	API 270	54	49-58	FR-VSP300UF350
Square	400	API 325	47	41.5-49	FR-VSP300UF400

The Continental Wire Cloth Difference

Continental Wire Cloth replacement shaker screens offer the oil industry a superior product—longevity, increased flow, durability and competitive prices.

make **The Black Screen™**
your last screen

Continental Wire Cloth does not manufacture screens for NOV Brandt®. CWC manufactures replacement screens that give our customer an alternative option for their solids control needs. Standard mesh sizes are listed above. For other available sizes, please contact our sales department.

* Results from in house testing.